SERIAL NO.:

10/812,660

March 29, 2004

FILED: Page 2

AMENDMENTS TO THE CLAIMS

Please add or amend the claims to read as follows, and cancel without prejudice or disclaimer to resubmission in a divisional or continuation application claims indicated as

cancelled:

1. (Currently Amended) A method for delivering information in a wireless network, the

method comprising:

receiving from a client application, a request for delivery of the information,

wherein the request includes a multicast address and a quality of service attribute;

checking an existence of said multicast address in a multicast schedule and updating

said multicast schedule or creating a new multicast schedule in response to the request

based on the existence of the multicast address;

coordingating a power saving protocol;

sending a response to the client application confirming scheduling of the request;

configuring a response and coordinating [[a]] said power saving protocol of the client to to

accomodate accommodates the scheduled multicast delivery of the information [[to]] with the

client application; and

sending the information to the client application according to the multicast schedule.

2. Cancelled.

- 3. Cancelled.
- 4. Cancelled.

5. (Original) The method of claim 1 further comprising:

deleting the multicast schedule after all clients associated with the multicast

schedule have been sent the information.

6. (Original) The method of claim 5 wherein deleting the multicast schedule comprises

receiving a deletion request from each client associated with the multicast schedule to

delete the multicast schedule.

SERIAL NO.:

10/812,660

FILED:

March 29, 2004

Page 3

7. (Currently Amended) The method of claim 1 wherein the wireless network comprises a wireless local area network (WLAN) and wherein the request comprises a transmission specification (TSPEC) request <u>including said multicast address and said quality of service</u> attribute.

- 8. (Currently Amended) The method of claim [[2]] <u>1</u> wherein the response comprises a <u>transmission specification (TSPEC) TSPEC</u> response.
- 9. (Currently Amended) A method of receiving information in a wireless network, the method comprising:

sending a request for delivery of the information, the request including a multicast designation address and a desired quality of service attribute;

receiving a response confirming that confirms a scheduled multicast delivery of the information to an application layer, the scheduled multicast delivery of the information created in response to the request for delivery of the information;

eonfiguring coordinating a power saving protocol to accommodate the scheduled multicast delivery of the information to awake state based on a multicast schedule; and receiving the information according to the scheduled multicast delivery.

- 10. Cancelled.
- 11. Cancelled.
- 12. Cancelled.
- 13. (Currently Amended) The method of claim 9 wherein the wireless network comprises comprising receiving the information over a wireless local area network (WLAN).
- 14. (Currently Amended) The method of claim 13 wherein comprising receiving the information over the WLAN uses orthogonal frequency division multiplexing (OFDM).

SERIAL NO.:

10/812,660

FILED:

March 29, 2004

Page 4

15. (Currently amended) The method of claim 9 wherein <u>sending</u> the request comprises sending a transmission specification (TSPEC).

16. (Currently Amended) The method of claim 9 further comprising sending a schedule deletion request to delete <u>from said</u> [[a]] multicast schedule.

17. (Currently Amended) A wireless communication apparatus comprising:

a processing circuit to coordinate a power saving mode of the apparatus with a multicast delivery schedule specified by a network device, wherein the processing portion includes

an application requesting media to request a multicast delivery of information;

a media access controller (MAC) operably coupled to the application requesting media to send a request including a multicast designation address and a desired quality of service attribute to delivery of deliver the multicast information from [[the]] a network device, to receive a notification from the network device that confirms a scheduled of the multicast delivery schedule, and to indicate confirmation of a scheduled multicast delivery of the information from the network device to an application layer [[,]]the scheduled multicast delivery of the information created in response to the request for delivery of information; and to coordinate a power saving protocol to accommodate the scheduled delivery of the information to an awake state of the communication apparatus based on a multicast schedule; and

a radio frequency (RF) interface <u>operably</u> coupled to the <u>processing circuit media</u> <u>access controller (MAC)</u> to transmit and receive the request and the information over an air interface.

- 18. (Cancelled)
- 19. (Cancelled)
- 20. (Cancelled)

SERIAL NO.: 10/812,660 FILED:

March 29, 2004

Page 5

21. (Previously Presented) The apparatus of claim 17 wherein the MAC is further configured to send a delete request message requesting removal of the apparatus from the multicast schedule.

22. (Previously Presented) The apparatus of claim 17 wherein the apparatus comprises a wireless user station (STA) and a network adaptor.

22. (Cancelled)

23. (Previously Presented) The apparatus of claim 17 further comprising: at least two antennas coupled to the RF interface.

24. (Currently Amended) A wireless communication apparatus comprising:

a processing circuit to determine a wireless multicast delivery schedule in accordance with power saving modes of multiple client devices and to notify the multiple client devices of the multicast delivery schedule; and

wherein scheduling of the wireless multicast is based on one or more requests having a multicast address and received from one or more network devices, and a power saving protocol of the multiple clients is configured to accommodate the scheduled multicast delivery. receive from a client application a request for delivery of information, wherein the request includes a multicast address and a quality of service attribute, to check an existence of said multicast address in a multicast schedule, to update said multicast schedule or to create a new multicast schedule based on the existence of the multicast address, to coordinate a power saying protocol, to send to the client application a response and to coordinate said power saving protocol to accommodate the scheduled multicast delivery of the information to the client application and to send the information to the client application according to the multicast schedule.

25. (Currently Amended) The device apparatus of claim 24 further comprising:

SERIAL NO.:

10/812,660 March 29, 2004

FILED: Page 6

[[an]] a radio frequency (RF) interface operably coupled [[with]] to the processing

circuit and configured to transmit the wireless multicast information to the client application

according to the schedule determined by the processing circuit.

26. (Original) The apparatus of claim 24 wherein the apparatus comprises a wireless local

area network (WLAN) access point.

27. (Cancelled)

28. (Previously Presented) The apparatus of claim 24 wherein the processing circuit is to send

the schedule to one or more requesting network devices as a transmission specification

(TSPEC) response.

29. (Currently Amended) The apparatus of claim 24 wherein the processing circuit is

[[further]] configured to buffer application data packets for the wireless multicast until a time

indicated on the multicast schedule.

30. (Original) The apparatus of claim 25 further comprising:

at least two antennas coupled to the RF interfaces for enabling multiple input

multiple output (MIMO) communications.

31. (Currently Amended) A wireless communication system comprising:

a radio frequency (RF) transceiver;

at least two antennas electrically coupled to the RF transceiver; and

a [[data]] processing circuit electrically coupled with the RF transceiver, wherein

the [[data]] processing circuit is to determine a wireless multicast delivery schedule in

accordance with power saving modes of multiple client devices and to notify the multiple

client devices of the multicast delivery schedule; and

wherein scheduling of the wireless multicast is based on one or more requests

having a multicast address and received from one or more network devices, and a power

saving protocol of the multiple clients is configured to accommodate the scheduled multicast

SERIAL NO.:

10/812,660

Page 7

March 29, 2004 FILED:

delivery receive from a client application a request for delivery of information, wherein the request includes a multicast address and a quality of service attribute, to check an existence of said multicast address in a multicast schedule, to update said multicast schedule or to create a new multicast schedule based on the existence of the multicast address, to coordinate a power saving protocol, to send to the client application a response and to coordinate said power saving protocol to accommodate the scheduled multicast delivery of the information to the client application and to send the information to the client application according to the multicast schedule.

32. (Cancelled)

33. (Currently Amended) The wireless communication system of claim 31 wherein the requests comprise a transmission specification (TSPEC) including a multicast address and a quality of service (QoS) indicator.

34. (Currently Amended) The wireless communication system of claim 31 wherein the communication system comprises a wireless local area network (WLAN) access point (AP).